

## ISUZU CITIPORT12 CNG

Manufactured by Anadolu Isuzu


The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

## CITIPORT 12 CNG

## TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	
Dimensions (mm)	
Maximum Length	12030
Maximum Width	2550
Maximum Height	3398 (inc. CNG tanks)
Wheelbase	5850
Front Overhang	2700
Rear Overhang	3480
Weights (kg)	18700
Gross Vehicle Weight  Engine	16700
Model	Cummins L9NE6E320
Type	CNG Turbocharged
Number of Cylinders	6
Displacement (cc)	8880
Maximum Power (kw(PS)/rpm)	208 (282) / 2000-2100
Maximum Torque (Nm/rpm)	1236 / 1300-1400
Emission Standard	Euro VI OBD-E
Transmission	
Model	ZF 6 AP 1400 EMF
Number of Gears	6 Forward, 1 Reverse
Steering System ————————————————————————————————————	Hydraulic and Adjustable Dashboard and Steering
Tyres	Wheel Column in Height and Inclination
Tyre Sizes	275/70 R22,5
Suspension	2707701122,0
Front	Independent Air Suspension, 2 Air Bellows,
Tiont	2 Hydraulic Shock Absorbers
Rear	Air suspension - 4 bellows
	electronically controlled (ECAS)
Anti Roll Bar	S
Kneeling System (ECAS & ELC)	S
Brake System	
Front / Rear	Disc / Disc
System	Full Air Brake System With EBS
	(Automatic Oil, Water Seperator System is Optional
Parking Brake	Air Actuated Acted on Rear Axle
Auxiliary Brake	Intarder
Fuel Tank	5 000 H (4 (00 H) T 00 0H0 (H0)(4 0 H0)(9)**
Gas Tanks Capacity (L)	5 x 320 lt (1600 lt) - Type 3 CNG (NGV1&NGV2)**
Gas Filling Port	Compatible with NGV2
Electrical System	0.077/0.4070
Battery Canacity*	24V (2x12V) - 240 Ah
Passenger Capacity*	01
Maximum Passenger Capacity	91
Standard Layout	27 Seated (3 Foldable Seats) + 64 Standing
Optional Seat Layouts	24 Seated + 1 Wheelchair + 63 Standing





## **FOUIPMENTS**



EQUIPMENTS		
Heating and Ventilation		
Pre Heater Air Conditioner	Opt	
Digital Air Conditioner		
A/C With Heater	Opt	
Safety & Driving Comfort		
Speed Limitor	S S	
Tachograph ABS	S	
ASR	S S S S S S S S S S S S S S S S S S S	
EBS EBD	S	
Bus Stop Brake (BSB)	S	
Hillholder	S	
Retarder Parking Sensor	S	
Spare Wheel	S	
Tyre Inflation Set	S	
Roof Hatch for Ventilation & Emergency Exit	S (1 Units with Electrical Control) S	
Reverse Gear Warning Beeper Fire Extinguisher	S	
Engine Compartment Fire Detection		
and Automatic Fire Supression System	S S (Front / Rear)	
Fog Lamps Day Time Running Lamps (DRL)	S (FIGURA Red)	
Locking System	S (0: Square Lock)	
Battery Main Switch	S	
Exterior	0.1	
Metallic Paint Side Stripe Stickers	Opt Opt	
Skid Plate	S	
Towing Device	S	
Doors Number of Service Doors	3 Doors (S), 2 Doors (Opt)	
Type of Service Doors	DoubleWing Air Actuated Interior Movement for All Front,	
W	Middle and Rear Doors	
Wheelchair Ramp Wheelchair Ramp Sensor	Side Kneeling System and Ramp S	
Remote Control	S (Front Service Door)	
Windows —	New Aldies 1// History Decrease Windows	
Туре	Non-sliding, 1/4 Hinged Passenger Windows, Single Piece (S), With Slider, Double Piece (Opt)	
Layers of Glass	Single Glazed (S), Double Glazed (Opt)	
Interior		
Driver Seat		
Windshield Blind Driver Curtain	S S	
Driver's Seat	Air Actuated, Adjustable	
Electrically Controlled Side Mirrors	S	
Heated Side Mirrors Driver's Cabin	S Semi Glass (S), Full Glass (Opt)	
Driver Overhead Cabinet	S	
Coathanger for The Driver	S Opt	
Ticket Validator Preperation Lamp for Driver Seat	S	
Passenger Compartment		
Passenger Seat Material	Cloth Ped On Plastic	
USB Charger for Passangers  Lightening & Signalization	Opt	
Interior Ceiling Lighting	S	
Stop Buttons & Signboard	S	
Digital Destination Display	Front, Rear (S), Colored (Opt)	
Audio & Visual	c	
Camera Systems Camera Monitor on Dashboard	S S S Radio, USB, MP3	
Recording Device (DVR)	S Dedie UCD MD2	
Radio System Monitor / LCD Screen (Passenger Compartment)	Kadio, USB, MP3 S	
Digital Clock	S S S Opt Standard Ont: Ontional	
Driver Speaker Announcement System for Passenger Area	Opt Co Charactered Onto Outlinear	
2 of the control of the con	S: Standard Opt: Optional	

<sup>\*\*</sup>This option may increase the maximum height of the vehicle

<sup>\*</sup> Different seating variations are available.

